



Fire Apparatus Quotation for: OCALA FIRE RESCUE



Quotation Number: 150761 Rev: 20

Unit Description: RELN-COMM

Quote Description: Light Rescue Non Walk-In Alum, Commercial Chassis

Salesperson: JRICE2

Salescode	Extended Description	Qty	
TESTING COMPLIANCE STANDARD			
1001-0017	Unit is part of a multiple order. Production order numbers are:	1	
1001-0100	Prior trucks for this customer include the following shop order(s):	1	
1001-0103	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1900, 2024 edition.	1	
3090-0002	OAH. Unit has no overall height restrictions.	1	
3090-0004	OAL. Unit has no overall length restrictions.	1	
3340-1137-12C	Equipment allowance on the apparatus shall be 2500 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1	
CHASSIS PREP			
1020-0023	Commercial Chassis Preperation for the Ford Super Duty Series.	1	
1020-0024	Ember Seperator - Ford.	1	
1020-0075	Commercial chassis administrative, processing and handling for Ford Series or similar chassis.	1	
TIRE OPTIONS			
1060-0117	RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications.	1	
AIR SYSTEM OPTIONS			
1110-0046	Kussmaul 12V Auto Drain. For use with Kussmaul air compressor.	1	
ENGINES & TRANSMISSIONS			
1200-0025	Speed maximum 75 MPH. Note: Speed rating may be lower based off OEM tire ratings provided on chassis. (Requires signed NFPA exception letter on trucks above 26,000 GVRW.)	1	

Salescode	Extended Description	Qty	
ENGINES & TRANSMISSIONS			
1200-0438	FORD F550 7.3L V8 Gasoline Engine	1	
EXHAUST OPTIONS			
1225-0024	Plymovent Grabber magnetic exhaust end. Bolt-on for exhaust extraction system.	1	
CHASSIS OPTIONS			
1680-0075	Receiver, (3) way rear underbody assembly. Includes rearward 9000 lb. winch receiver / Class III trailer hitch receiver and (2) side facing 9000 lb. winch receivers - (1) each below rearward body compartments, rearward tow eyes and electrical winch connections for each receiver. NOTE: When facing receiver(s) locate electrical connection to the left side.	1	
1680-0215	Diamond plate running boards with Gator Grip for 2 door extended cab Super Duty Ford chassis.	1	
CAB			
1500-0051	Ford Commercial Super Duty Cab (aluminum) and Chassis 2 door EXT F550 4X2. Rear doors limited to 90 degree opening with OEM lock-out kit.	1	
CAB BADGE PACKAGE			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
CAB DOOR OPTIONS			
1550-0227	Reflective striping shall be installed on commercial cab doors, visible when the door is open, meeting NFPA requirement of 96 sq. in. coverage for each door. Colors to match rear chevron.	1	
MISC EXTERIOR CAB OPTIONS			
1675-0120	Unleaded fuel only label.	1	
SEATS			
1685-0032	Seating capacity tag of five occupants.	1	
MISC INTERIOR CAB OPTIONS			
1685-0009	Chain for ignition key	1	
1685-0372	Map pocket rear cab console aluminum plate to match console finish.	1	
1685-0965	Center control console painted black Scorpion. Locate in cab between driver and officer. Includes area for NFPA siren, electrical, and in-cab controls (as applicable) switching.	1	

Salescode	Extended Description	Qty	
CAB ELECTRICAL OPTIONS			
1750-0024-495-04	Auto-Eject receptacle inlet 20 amp located driver side body wheel well offset forward with a Yellow cover.	1	
1750-0161	Air compressor, Kussmaul model 091-9B-1, 120V.	1	
1750-1003	Battery charger Kussmaul Chief Series. 120/240 volt inlet, 40 amp output. Includes built-in touch screen display.	1	
1750-1007-495-04	A Yellow Super Auto Eject Deluxe Cover with OLED display, for the auto eject located driver side body wheel well offset forward. 20A receptacles only. Kussmaul Chief chargers only without external display(1750-1003).	1	
BODY SPEC			
3090-0052	Extruded aluminum rescue body spec EA	1	
RESCUE BODY LOWER			
3092-0010-003	Extend diamond plate floors out to door opening. Location is L1. Extruded aluminum.	1	
3092-0010-015	Extend diamond plate floors out to door opening. Location is R1. Extruded aluminum.	1	
3092-0119	10' Non Walkin Rescue Rear Module 24/48/36 EA. Light rescue only. Includes spring hanger notches if needed.	1	
RESCUE BODY UPPER			
3094-0094	Body Height, Upper 13". Extruded Aluminum. Side facing upper body panel will be 10" above the body compartments for light mounting.	1	
3094-0096	Diamond plate flat roof. Light rescue body only.	1	
RESCUE BODY REAR			
3096-0004	10" Tailboard Bolt-On With Bracing Rescue	1	
3096-0019	Rescue Rear Body with single compartment above the frame rails 48" wide. The compartment will run to under the roof line extrusion. Light rescues only.	1	
BODY COMPT REAR			
3110-0028	Rear body panels to be painted smooth plate.	1	
RESCUE BODY OPTIONS			
3360-0020	Front body panels to be diamond plate.	1	
DOORS			
3300-0007-003	Door single vertical hinged painted. Location(s): L1	1	
3300-0007-015	Door single vertical hinged painted. Location(s): R1	1	

Salescode	Extended Description	Qty	
DOORS			
3300-0011-004	Door single horizontal hinged lift-up box pan configuration painted. Location(s): L2	1	
3300-0011-016	Door single horizontal hinged lift-up box pan configuration painted. Location(s): R2	1	
3300-0292-005	Door double 3-point vertical hinged w/rotary latches - painted. Location(s): L3. Includes latch handle extension installed on secondary door's interior latch with "PULL" tags using .125 plate.	1	
3300-0292-017	Door double 3-point vertical hinged w/rotary latches - painted. Location(s): R3. Includes latch handle extension installed on secondary door's interior latch with "PULL" tags using .125 plate.	1	
3300-0292-027	Door double 3-point vertical hinged w/rotary latches - painted. Location(s): B1. Includes latch handle extension installed on secondary door's interior latch with "PULL" tags using .125 plate.	1	
3300-0346-30M	Tri-Mark door latch IPO standard. Non-Locking, Powder coated black. Location(s): Inside or on body per customer approval drawing.	7	
SHELVES			
3370-0043	Unistrut. All exterior compartments on rescue body will have Unistrut in each compartment unless inapplicable.	1	
3370-0045	Shelf, adjustable. Locate: B1 above frame rails.	1	
TRAYS / TOOLBOARDS			
3380-0654-004	Floor mounted steel SlideMaster roll-out/tilt down model SMT powder coated silver with aluminum tray. For use on single depth or rescue style compartment trays. NOTE: With lift-up door, tray latch to be offset as required to clear striker. L2 floor.	1	
3380-0654-016	Floor mounted steel SlideMaster roll-out/tilt down model SMT powder coated silver with aluminum tray. For use on single depth or rescue style compartment trays. NOTE: With lift-up door, tray latch to be offset as required to clear striker. R2 floor.	1	
3380-0656-027	Floor mounted steel SlideMaster model SM3-SP powder coated silver with aluminum tray. Location: B1.	1	
3380-0658-650	Floor mounted Bi-Directional SlideMaster with tray. Model SM2-D-SP Steel powder coated silver. Mounted on floor of L1/R1 transverse.	1	
MISC BODY OPTIONS			
1675-0158-078	Backboard storage sleeve for (1) board. Includes retaining strap for board. Loc: L2 upper.	1	
3340-0077	Body compartment Interiors to have multi-tone gray finish. To include pan of	1	

Salescode	Extended Description	Qty	
MISC BODY OPTIONS			
	hinged doors and tool compartments (as applicable). Does not include floors if they are diamond plate. Does not include roof top compartments if equipped.		
3340-0088	Smooth plate single axle wheel well painted job color. Includes bolt-on composite wheel well liners.	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0147	Louver Guards. All lower body compartment louvers to have protective guard provided on exterior of compartments to prevent road spray from entering compartments.	1	
3340-0152-000-02	Dri-Dek brand Red floor matting covering all applicable compartment floors, shelves, and rollout trays. Does not include roof top compartments (Added separately)	1	
3340-0174-078	Stokes basket storage compartment. Locate in L2 upper with a strap(s) to hold basket in rack.	1	
3340-0671	Recessed fuel fill driver side wheel well supplied by Ford.	1	
3340-1648	Anodized aluminum trim on bottom edge of all body compartment openings including pump enclosure if applicable with painted edges.	1	
3340-1719	Rubrails constructed of 3" x 2" Black U.H.M.W. polyethylene bolted to the lower exterior edge of the apparatus. Includes pump module sides, body sides and rear body/tailboard as applicable. Rubrails shall be mitered 45 degrees at leading and trailing end and notched for lighting and other rubrail mounted options. Includes strip of embossed diamond plate on top surface of rubrail in stepping areas (finish to match stepping surface).	1	
ELECTRICAL SYSTEMS			
5010-0094	Nanoprotech (or equivalent) corrosion inhibiting spray coating to be applied on all exposed electrical connections.	1	
5010-0153	ControlMaxx Electrical system for pumper / tanker / rescue / ARFF.	1	
5010-0158-B13	10" display for multiplex electrical system. Location: center console.	1	
LIGHT BARS			
5300-0504	Whelen MKEZ7 1.5" standard mount for front light bar (PR).	1	
5300-0506-000-4V	Front light bar LED color: Red/White with clear lenses (If applicable, includes side facing when colors are the same.)	1	
5300-0522	Light bar Whelen Freedom IV Model F4X0 60" with 8 LED modules. Location: Centered on the front cab roof.	1	
WARNING LIGHTS			
5600-0105-B13	Hazard (door ajar) light 2" LED. Location: center console.	1	

Salescode	Extended Description	Qty	
WARNING LIGHTS			
5600-0346	All warning lights to have black bezels ipo chrome where applicable.	1	
5600-0789-3RG-4T	Warning/ground and/or scene light Whelen M6V2 series Linear Super LED (PR). Location: (1) each side NFPA/ULC required lower zone midship side facing, color will be RED with CLEAR lenses.	1	
5600-0789-467-4T	Warning/ground and/or scene light Whelen M6V2 series Linear Super LED (PR). Location: (1) each side above tail lights, color will be RED with CLEAR lenses.	1	
5600-0958-3RE-4T	Warning light Whelen 600 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone front facing.	1	
5600-0958-3RI-4T	Warning light Whelen 600 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone rear facing.	1	
5600-0958-457-4T	Warning light Whelen 600 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side of body rear facing up high.	1	
5600-0959-457-4U	Warning light Whelen 900 series Super LED (PR). Color: RED with RED lenses. Location: (1) each side of body rear facing up high.	1	
5600-0959-G98-4T	Warning light Whelen 900 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side of body side facing upper forward.	1	
5600-0959-G99-4U	Warning light Whelen 900 series Super LED (PR). Color: RED with RED lenses. Location: (1) each side of body side facing upper rearward.	1	
5600-1037-3RF-4T	Warning light Whelen T-Series model TSS0 Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone forward side facing. (Split light head(s) not available) Note: T-Series light only available with clear lenses.	1	
5600-1037-3RH-4T	Warning light Whelen T-Series model TSS0 Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone rear side facing. (Split light head(s) not available) Note: T-Series light only available with clear lenses.	1	
5600-1037-469-4T	Warning light Whelen T-Series model TSS0 Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side centered below forward compartments in rubrail if equipped. (Split light head(s) not available) Note: T-Series light only available with clear lenses.	1	
5600-1037-471-4T	Warning light Whelen T-Series model TSS0 Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side just behind rear wheels in rubrail if equipped. (Split light head(s) not available) Note: T-Series light only available with clear lenses.	1	
5600-1037-5YI-4T	Warning light Whelen T-Series model TSS0 Super LED (PR). Color: RED with CLEAR lenses. Location: on cab/bumper as specified. (Split light head(s) not available) Note: T-Series light only available with clear lenses.	2	

Salescode	Extended Description	Qty	
DIRECTIONAL LIGHT BARS			
5310-0012	Diamond plate shield over rear directional light.	1	
5310-0017	Whelen Traffic Advisor model TAL65 LED - 36" long.	1	
5310-0020-B13	Directional light bar control is to be located center console.	1	
5310-0025	Directional light circuit wiring through upper level warning.	1	
SIRENS			
5500-0015	Whelen model 295SLSA1 siren with microphone (replaced 295HFSA1).	1	
5500-0024-B13	The primary electronic siren control is to be located center console.	1	
SPEAKERS			
5510-0034-209	Whelen SA315P electronic siren speaker mounted behind front bumper cut-out. Location: driver side front bumper.	1	
DOT LIGHTING			
5150-0125	Marker light .75" Dia LED body package. Commercial light rescue or initial attack vehicle bodies.	1	
5150-0154	License plate light EON LED located at the rear of the body.	1	
5150-0271	Bracket license plate at rear of body. Smooth plate sanded bracket.	1	
5150-0289	Whelen 600 series LED vertical mount tail lights. Includes LED stop/tail, turn and back-up lights with vertical chrome ABS 3 housing and weatherproof connectors. Requires turn signal flash pattern.	1	
5150-0297	All exterior mounted D.O.T. lighting to have bezels/brackets/covers black (painted as applicable) IPO chrome/stainless steel where applicable.	1	
5150-0299-5WD	Front (if applicable) and rear turn signal flash pattern: sequential arrow.	1	
LIGHTS - COMPARTMENT, STEP & GROUND			
5380-0200	Ground light package EON LED - small.	1	
5380-0203	Step light package body EON LED - small.	1	
5380-0560	Compartment light package ROM DuroStrip V5 LED for small bodies. Includes two lights per compartment (four if transverse).	1	
LIGHTS - DECK AND SCENE			
5390-0328	All scene lights lights to have black bezels ipo chrome where applicable.	1	
5390-0471-L01	Whelen 900 EZ series model 904SLC Gradient Opti-Scene light (PR) with weatherproof connectors. Switch in cab (driver and officer side lights switched separately). Locate officer side forward and rearward areas of upper panels on the body.	1	

Salescode	Extended Description	Qty	
LIGHTS - DECK AND SCENE			
5390-0471-L02	Whelen 900 EZ series model 904SLC Gradient Opti-Scene light (PR) with weatherproof connectors. Switch in cab (driver and officer side lights switched separately). Locate driver side forward and rearward areas of upper panels on the body.	1	
CAMERAS / INTERCOM			
5350-0060	Diamond plate camera shield.	1	
5350-0192	Safety Vision back-up camera wired through multiplex display. Video displays automatically when transmission is in reverse. Camera only - does not include monitor.	1	
5350-0561	Setcom LiberatorMAX wireless intercom with (4) headset chargers shall be installed within the cab. Headsets are not included and ordered separately (misc loose equip).	1	
MISC ELECTRICAL			
5110-0005	Pre-wire for trailer hitch. Includes stop, left turn, right turn, marker and ground wires. Does not include connector.	1	
5110-0017	Back-up alarm 97 dB.	1	
5110-0111	All 12 Volt electrical components and Multiplex box will be located in recessed box at rear between frame rails.	1	
5110-0219-663	Blue Sea 12V power distribution module model 5032. Location: L1 high on forward wall.	1	
5110-0219-762	Blue Sea 12V power distribution module model 5032. Location: behind officer's seat.	1	
5110-0219-B13	Blue Sea 12V power distribution module model 5032. Location: center console.	1	
LIGHTS - AREA			
5450-0632-060	Light Whelen 12V Pioneer Plus flood LED model PFH1B powder coated black with external bottom raise pole. Includes switch accessible to driver. Location(s): officer side front compartment face.	1	
5450-0632-062	Light Whelen 12V Pioneer Plus flood LED model PFH1B powder coated black with external bottom raise pole. Includes switch accessible to driver. Location(s): driver side front compartment face.	1	
MISC LOOSE EQUIPMENT			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	
EXTERIOR PAINT			

Salescode	Extended Description	Qty	
EXTERIOR PAINT			
8100-0181-000-7W	Paint body two-tone color - Sikkens paint: Color: As Specified.	1	
8100-0441	Repaint upper portion of Ford F550 or similar size commercial cab (roof, pillars, upper door frame only) as specified. Hood and lower cab not included.	1	
8100-0724	Paint steel wheels on Ford F550 or similar size chassis as specified . OEM steel wheels to be painted both inboard and outboard sides.	1	
8100-0775	Commercial cab to be painted by OEM as specified.	1	
8100-0838	PPG brand paint will be used on the E-ONE supplied components.	1	
8100-0839	Paint Body - Small - For Pumpers, Rear Mounts, S/A Tankers and Rescues (non-metallic). Color:	1	PPG 1002704 RED (FRD11:PQ Standard)
PROTECTIVE COATINGS			
8100-0495	LINE-X: One or more components installed on this unit shall have LINE-X coating. Color shall be Black unless otherwise specified.	1	
8175-0134	Poly-Elastomer (Line-X) coating shall be applied on the exterior of the body as specified by the customer. From four (4) to eight (8) square feet of surface painted. (EA)	15	
LETTERING			
8200-0115	Scotchlite Letter (Each) taller than 12". The exact size, color and location of the letters as specified by the customer.	2	
8200-0116	Shade and/or outline (EA) for letters as specified by the customer.	32	
8200-0118	Sign Gold Letter (Each) upto 12" tall. The exact size, color and location of the letters as specified by the customer.	30	
STRIPING			
8300-0145-000-J7	Chevron "A" style 6" 3M "Diamond Grade" striping on front bumper. Colors to be Red/Fluorescent Yellow Green.	1	
8300-0146-000-J7	Chevron "A" style 6" 3M "Diamond Grade" striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Red/Fluorescent Yellow Green.	1	
8300-0331	Single NFPA Scotchlite Stripe - up to 6" wide with hockey style, Z or S style or other customer specific design style. Stripe to be installed on cab and the body. Size, color and location as specified by the customer.	1	
8300-0334	Additional NFPA Scotchlite Stripe - up to 3" wide on cab and the body. Design, size, color and location as specified by the customer.	1	
8300-0340	Paint break Sign Gold cab stripe with outline - 3/4" wide total, gold with customer specified outline color. To be located above existing paint break.	1	
8300-0369	Single Sign Gold Stripe - upto 1" wide and non straight on cab and the body.	2	

Salescode	Extended Description	Qty	
STRIPING			
	Size, color and location as specified by the customer.		
GRAPHICS			
8400-0010-1V4	Install customer logo from an existing E-ONE design (EA). Location: reference graphics layout drawing	2	
8400-0060	Graphics drawing showing striping, lettering and logos. Requires E-ONE installed graphics.	1	
WARRANTY / STANDARD & EXTENDED			
9100-0117	General One (1) year or 24,000 Miles Limited Warranty (RFW0001)	1	
9100-0132	Electrical One (1) Year or 18,000 Miles Limited Warranty (RFW0201).	1	
9100-0136	Body Structure Aluminum Ten (10) years or 100,000 Miles Limited Warranty (RFW0502).	1	
9100-0140	Paint and Finish (Exterior Clear coated) Ten (10) Years Limited Warranty (RFW0710).	1	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0009	Manuals, Operator and Service in digital format.	1	
9300-0016	Approval Drawings-Standard.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	
Dealer Supplied Equipment			