



June 9, 2026
 Our 97th Year

Ship To:
 CITY OF OCALA
 1805 NE 30TH AVE
 BLDG 200
 OCALA, FL 34470
 US

Bill To:
 CITY OF OCALA
 151 SE OSCEOLA AVE
 FINANCE DEPT
 OCALA, FL 34471
 US

Attn:
 Phone:
 Email:

Attec Sales Order: 8694153
Attec Quotation Number: 1941719 - 1
Run Number: 1528329
Account Manager: Jake Lewellen
Technical Sales Rep: Jesse C Boyd
Reference WO: New Spec-
Customer Inspection:
Customer Truck Number:

X7 Discrete Job: 1045417169
X7 Configured Item: 000067005-42971649
Quantity: 1
X4 Discrete Job:
X4 Configured Item:
System Engineer:
Structural Engineer:
Line Set Date: 06/18/2025

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<u>Unit</u>	
1.	The Attec trailer mounted TS20-4P is a four drum puller. This trailer-mounted overhead cable puller is capable of pulling four conductors individually. Unit is capable of pulling up to 2,000 lb with a max line speed of 4.5 mph. The unit is equipped with 8,000 ft of 1/2 in rope on each pulling drum. Each drum of rope is color coded. This unit is built in accordance with Attec's standard specifications and includes the following features:	1
2.	Trailer frame and tongue is constructed of tubular steel and is fully welded. Includes full rear fenders. Dimensions: 18 ft 5 in length, max width 8 ft 0 in, travel height 8 ft 9 in	1
3.	Kubota Tier 4 Final, 49.6 hp diesel engine. No DPF, DEF or regen required	1
4.	Spring mounted single axle (9,000 lb capacity) with electric brakes	1
5.	Two (2) wheel/tire combos (235/75/R17.5)	1
6.	Trailer is equipped with 2.5 in ID adjustable pintle eye, adjustable between 17.5 in - 30.5 in from ground, 42,000 lb MGTW, 7,000 lb vertical load. Safety chains: Two (2) safety chains with hooks and safety latches are installed on the trailer tongue. Safety breakaway switch installed on the trailer tongue	1
7.	15 gal hydraulic oil reservoir, 20 gal fuel tank	1
8.	Standard hydraulic oil, ISO 46 grade	40
9.	Operator control station centrally locates all controls for the unit and is located at the front of the trailer. The operator station has a protective screen and adjustable operator seat. The controls are fully hydraulic and utilize pilot pressure lines for increased meterability. The unit's control functions include pay in/pay out speed, motor park brake, pulling pressure, levelwind selector, levelwind control, fuel gauge, engine key switch, and engine controls (start/stop, throttle, etc.)	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
10.	Four levelwinds, one dedicated to each pulling drum, are mounted to the rear of each drum with individual hydraulic actuation	1
11.	Chain drive system: The hydraulic motor drives the two arbor bars through use of a chain. Rotationally fixed couplers (located on the exterior perimeter of the trailer) are used to engage the desired drum	1
12.	Arbor bar: 2.5 in diameter arbor bars. Each arbor bar assembly to be equipped with a drive sprocket, two pulling drum assemblies and two drum couplers	1
13.	Overspin payout brake: 18 in non-rust bronze disc located on the external side of each drum	1
14.	Each drum equipped with 8,000 feet of 1/2 in color coded rope	1
15.	One (1) hydraulically driven jack with pilot operated holding valve, holds jack in place even in the event of a hydraulic failure, located at tongue of trailer	1
16.	Two (2) hydraulic jacks located at rear of trailer, one each side	1
17.	All trailer lights are LED	1
18.	Standard trailer plug, 6 pin round connector	1
19.	Pulling Drum Cover	1
20.	Operator control station cover constructed out of aluminum. Dual grab handles with rubber hood latches for securement. Includes front jack plate with hooks for temporary storage when removed.	1

Body and Chassis Accessories

21.	Wheel Chocks, Rubber, 9.75" L x 7.75" W x 5.00" H, with 4" L Metal Hairpin Style Handle (Pair)	1
22.	Vinyl manual pouch for storage of all operator and parts manuals	1

Finishing Details

23.	DOT Certification Required	1
-----	----------------------------	---

Sales Text: City of Ocala
1805 NE 30th AVE
Ocala, FL 34470

Last Updated By: Lisa a Chadwick on 07-MAY-2026 12:23

24.	Delivery Of Completed Unit	1
25.	Installation - TS20-4P	1
26.	Stock Unit	1

Miscellaneous

27.	Standard Warranty	1
-----	-------------------	---

Unit-----\$161,454
Shipping-----\$3,198
Total-----\$164,643

Altec Industries, Inc.

BY _____
Jesse C Boyd , Technical Sales Representative